




















Silent

Smartness

- Fluid Glass Sliding is suitable for all types of commercial & residential areas in variant sizes.









06F18001

### **Automatic Sliding Door System**

### **SPECIFICATION**

- Automatic Sliding Door System
- Multiple Use Commercial & Residential places
- Multiple Function with Remote Control Feature
- Smooth & Long Lasting
- Length : 4.2mtr.
- Finish : Alu.





#### **AUTOMATIC SLIDING DOOR SYSTEM**

#### **PRODUCTS FEATURES**

The microcomputer control adopts German technology, so it can detect weight and size of the door quickly and accurately. Optimal parameters can be set for it to keep the door in the best condition. Running condition of the door can be remembered. Besides, it has adjusting function and is highly intelligentized.

The remote control function, state and reliable.

the width power source, low power consumption, efficiency high performance, is stable.


Adopt brush less DC Motor and turbine worm reducer, high torque, high efficiency, long operating life.

Best humanity design, good safety, has encounter obstacles protection detection function.

Motor lock function, when door fully closed, remain closing, need not electric \*switch) lock.

Half open function, can set opening position freely. Cooperate with various of access control mode. The high quality post sale service.





Aluminium Rail Size







Up & Down Connection Bracket



Glass clamp



Hanging group, roller and hanging parts



Control module



Motor


#### TECHNICAL SPECIFICATION

Туре	Single Door	Double Door	
Model	HD150-S	HD150-D	
Loading Capacity	≤ 120KGS	≤ 2X120KGS	
Power Supply	AC160-250V 50-60Hz		
Sensor Type	Compatible with sensors of various models		
DC Motor	DC 24V 2200 RPM Geared Motor (60W/90W)		
Standard Rail Length	2000mm	4000mm	
Minimum Clear Width	500mm	1000mm	
Maximum Clear Width	2000mm	3500mm	
Opening Width	100% (Full open) / 20% (Adjustable)		
Opening Speed	100mm-500mm / sec (Adjustable)		
Closing Speed	100mm-500mm / sec (Adjustable)		
Hold Open Time	0-410 sec (Adjustable)		
Force Needed for Manual Opening and Closing	<40N	<50N	
Ambient Temp	-20°C to +50°-C		




#### FLUID CARRIER 31 WITH DOUBLE DAMPING SYSTEM

Item Code	Package Fitting (2 mobile door + 1 fixed door)				
2 + 1		<u>∞</u> x2 <u>*****</u> x2		XI	
06F17042	Upper roller with damp	Damp stopper	Upper roller	bottom roller	
Glass Door	<u> </u>		x1	<b>© ©</b> x2	
3 + 1					
06F17043	Up-down hanging plate 1 Up-dowr	n hanging plate 2 Connected bo	ottom roller Fixed door up guider	Fixed door bottom guider	
Glass Door					
4 + 1 <b>06F17044</b>	Steel wire connector	Connector	Steel wire fixing part	Steel wire	
Glass Door		O O X6	NE NE		
		Glass clamp 1	Decorative cover		



















#### PRODUCT DESCRIPTION

- Door up & Down adjusting device: no need to unload door, but just use cross screwdriver to adjust door up & down
- Smooth, steady and silent movement: Damping function exists while door opening and door closing
- Multi Door linkage function.
- Adjustable stopper device: Adjustability for convenient operation; secure and steady function during door sliding.
- Application range: glass door
- Glass Thickness: 5mm


#### **PRODUCT APPLICATION**






#### FLUID CARRIER 45 WITH DOUBLE DAMPING SYSTEM (1 DOOR KIT)












#### FLUID CARRIER 55 WITH DOUBLE DAMPING SYSTEM (1 DOOR KIT)



#### TRACKS (Pcs)














#### FLUID CARRIER 56 WITH DOUBLE DAMPING SYSTEM (1 DOOR KIT)









### 06F14101

#### To Mount the Track with Glass




#### **SPECIFICATION**

- Countersunk Hole for Better Holding

- Suitable to Use with 10mm & 12 Mm Glass

- Material : SS 304 - Finish : SSS



### 06F14102

#### To Hold the Track with Wall




#### **SPECIFICATION**

- Track Mounting Bracket
- Flat Face
- Material : SS 304





#### FLUID CARRIER 57 FOR HEAVY HANGING ROLLER (1 DOOR KIT)

Item Code	Package Fittings			
06F17401 GLASS DOOR (One Door Kit)	X2	X1	13   23   S   43   43	GLASS PREPARATION
	60		26.8 0 0 0 1 1 2 1 1 2	<b>1</b> 2










#### TRACKS (Pcs)





#### FLUID CARRIER 58 FOR HEAVY HANGING ROLLER (1 DOOR KIT)



Item Code	Package Fittings				
06F17402 GLASS DOOR (One Door Kit)	X2	x		13   23   S   43   43	GASS PREPMANTON
	l· (	78 000 1-29 r	26.8 1 1 1 1 1 - 1 8 - 12		x2







#### TRACKS (Pcs)

